

Drive Shaft

Model	Shaft Torque (N.m)	Shaft Diam. D (mm)	Max. Distance Between Supports (mm)	Maximum Allowable (rpm)										
				Shaft Length L (mm)										
				900	1200	1500	1800	2100	2400	2700	3000	3300	3600	3900
CSD20L	5.65	20	1600	2350	1330	850	590	435	330	265	210	175	145	125
CSD25L	16.95	25	1900	2980	1675	1070	745	545	420	330	265	220	185	160
CSD30L	33.90	30	2150	3500	1990	1275	885	650	500	390	320	260	220	190
CSD35L	56.50	35	2350	4020	2265	1450	1000	740	565	445	360	300	250	215
CSD40L	101.70	40	2550	4665	2625	1680	1160	855	655	515	420	345	290	245
CSD45L	169.50	45	2800	5300	2980	1900	1325	970	745	585	475	390	330	280
CSD50L	254.25	50	3000	5865	3300	2110	1465	1075	825	650	525	435	365	310
CSD55L	367.25	55	3200	6430	3620	2315	1600	1180	905	715	575	475	400	340
CSD60L	508.50	60	3400	6975	3925	2510	1745	1280	980	775	625	515	435	370
CSD65L	678.00	65	3550	7500	4215	2700	1875	1375	1055	830	675	555	465	400

Note:

1. Exceeds maximum distance between supports. Pillow blocks are required.
2. Maximum allowable RPMs is based on 80% of critical shaft speed.

